Illinois - Flexibility Index Tester (I-FIT)





Features

- Accuracy- patented 2 CUDT system
- Immediately prints and plots test summary
- Includes ICT software for determining Flexibility Index (FI)
- 3 second runtime
- Simple Sample Preparation
- Most advanced hydraulics on the market



SPECIFICATIONS	
Dimensions (L x W x H)	31.5 in x 20 in x 58.5 in
Weight	350 lbs
Actuator Speed	1800 in/min
Force	4500 lbf
Stroke	2 in or 50 mm
Electrical Source	115 VAC / 20 Amp receptacle
Data Output	Test Advisor software or ICT software output

System Performance

Test Result

The user gets an immediate view of the data when the test completes.

Test data is formatted and saved to an output file compatible with Illinois Center for Transportation's (ICT) post processing software. The ICT software provides fracture energy and flexibility index calculation.





Information provided herein is based on test data believed to be reliable. In as much as Troxler Electronic Laboratories, Inc. has no control over the manner in which others may use this information, it does not guarantee the results to be obtained. In addition, Troxler does not make any express or implied warranty of merchantability or fitness for a particular purpose other than that for which the equipment is originally intended.

3008 E. Cornwallis Road Research Triangle Park, NC 27709 1-877-TROXLER (1-877-876-9537) 1-919-549-8661 (International) www.troxlerlabs.com

Made in USA